



## Heavy Plastic Protection Conduit With A Smooth Interior And Exterior; Liquid Tight; Spiral: Integrated Rigid Plastic



### Properties

IP 68 to EN/IEC 60529

Highly flexible

Good resistance to alkalis and acids

Good resistance to chemicals

Conforms to RoHS guideline

### Temperature range

-20 °C to 70 °C

Short time to 80 °C

### Delivery variants

Futher diameters and lenghts available on request

Grey (standard)

### Design material

Hard plastic spiral integrated in wall; spiral: rigid PVC; Wall: High grade soft PVC

### Get in contact with our team in The Netherlands or Belgium

#### The Netherlands

Freddy van Riemsdijkweg 7  
5657 EE Eindhoven

+31 (0)40 20 88 088  
sales@avt-connecting.com  
www.avt-connecting.com

#### Belgium

Grauwmeer 1/45 Bus 43  
B-3001 Heverlee

+32 (0)16 400 500  
sales@avt-connecting.be  
www.avt-connecting.com

## Heavy Plastic Protection Conduit With A Smooth Interior And Exterior; Liquid Tight; Spiral: Integrated Rigid Plastic

Nominal width connecting part mm	I.D. mm	O.D. mm	Bending Radius (middle of hose) mm	Weight kg/m	PU m
14	10	14	56	0,100	10
14	10	14	56	0,100	50
17	13	17	68	0,120	10
17	13	17	68	0,120	50
19	15	19	76	0,140	10
19	15	19	76	0,140	50
21	16	21	84	0,160	10
21	16	21	84	0,160	50
27	22	27	108	0,250	10
27	22	27	108	0,250	50
36	30	36	144	0,400	10
36	30	36	144	0,400	25
45	38	45	180	0,520	10
45	38	45	180	0,520	25
52	45	52	208	0,660	10
52	45	52	208	0,660	25
56	49	56	224	0,700	10
56	49	56	224	0,700	25

### Get in contact with our team in The Netherlands or Belgium

#### The Netherlands

Freddy van Riemsdijkweg 7  
5657 EE Eindhoven

+31 (0)40 20 88 088  
sales@avt-connecting.com  
www.avt-connecting.com

#### Belgium

Grauwmeer 1/45 Bus 43  
B-3001 Heverlee

+32 (0)16 400 500  
sales@avt-connecting.be  
www.avt-connecting.com

