


Light Plastic Protection Conduit With A Smooth Interior; Liquid Tight; Spiral: Integrated Rigid Plastic



Properties

IP 68 to EN/IEC 60529

Highly flexible

Good resistance to alkalis and acids

Good resistance to chemicals

Conforms to RoHS guideline

Temperature range

-20 °C to 70 °C

Short time to 80 °C

Delivery variants

Futher diameters and lenghts available on request

Grey (standard)

Design material

Hard plastic spiral integrated in wall; spiral: rigid PVC; Wall: High grade soft PVC

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com



Light Plastic Protection Conduit With A Smooth Interior; Liquid Tight; Spiral: Integrated Rigid Plastic

Nominal width connecting part mm	I.D. mm	O.D. mm	Bending Radius (middle of hose) mm	Weight kg/m	PU m
10	7	10	15	0,050	10
10	7	10	15	0,050	50
14	10	14	21	0,060	10
14	10	14	21	0,060	50
17	13	17	26	0,070	10
17	13	17	26	0,070	50
19	15	19	29	0,100	10
19	15	19	29	0,100	50
21	16	21	32	0,120	10
21	16	21	32	0,120	50
27	21	27	41	0,200	10
27	21	27	41	0,200	50
36	29	36	54	0,250	10
36	29	36	54	0,250	25
45	38	45	68	0,380	10
45	38	45	68	0,380	25
56	48	56	84	0,480	10
56	48	56	84	0,480	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

