


Plastic Coated, High Flexible Metal Protection Conduit; Robust and Liquid Tight; Hooked Metal Profile



Properties

IP 68 to EN/IEC 60529

Good resistance to oil, gasoline and chemicals

Good resistance to alkalis and acids

Increased resistance to tear, pressure and impact

Flame-retardant

Conforms to RoHS guideline

Highly flexible

Temperature range

-20 °C to 70 °C

Short time to 80 °C

Delivery variants

Further diameters and lengths available on request

Grey (standard)

Special colours: Full coloured

Customer-specific branding

Design material

Profiled metal strip, galvanised steel; hooked profile; wall: High grade soft PVC

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Coated, High Flexible Maetal Protection Conduit; Robust and Liquid Tight; Hooked Metal Profile

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Dyn. Bending Radius	Weight kg/m	PU
- *	5	8	26	29	0,06	50
- *	6	9	29	34	0,07	50
10	7	10	32	40	0,08	10
10	7	10	32	40	0,08	50
- *	8	11	35	43	0,09	50
- *	9	12	38	45	0,12	50
14	10	14	40	48	0,14	10
14	10	14	40	48	0,14	50
- *	11	15	42	50	0,15	50
17	13	17	45	55	0,17	10
17	13	17	45	55	0,17	50
- *	14	18	49	57	0,18	50
19	15	19	52	60	0,19	10
19	15	19	52	60	0,19	50
21	17	21	58	75	0,23	10
21	17	21	58	75	0,23	50
- *	18	22	61	79	0,24	50
27	22	27	72	90	0,38	10
27	22	27	72	90	0,38	50
- *	23	28	76	93	0,40	50
36	29	36	98	110	0,53	10
36	29	36	98	110	0,53	25
- *	31	38	102	115	0,56	50
45	38	45	118	140	0,71	10
45	38	45	118	140	0,71	25
- *	40	47	121	148	0,75	50
52	45	52	130	165	1,00	10
52	45	52	130	165	1,00	25

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Dyn. Bending Radius	Weight kg/m	PU
- *	47	54	135	170	1,04	50
56	49	56	140	175	1,08	10
56	49	56	140	175	1,08	25
- *	51	58	145	182	1,14	50

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com