


Shrink Ratio Single-sided Printable PermaSleeve Wire Markers

3:1 Shrink Ratio Single-sided Printable PermaSleeve™ Wire Markers



PermaSleeve markers fit snugly around wires for maximum insulation protection and permanent identification.



Brady PermaSleeve full-circle insulating wire markers meet the rigid insulating, material requirements and physical properties of MIL-DTL-23053/5 Class 1, MIL-M-81531, MIL-STD-202F, METHOD 215, and UL224. The heat-shrinkable irradiated polyolefin does not smudge or fade when printed. The unique flattened full-circle design provides fast, permanent wire marking. PermaSleeve markers may be printed on Brady's thermal transfer printers.

White Polyolefin (B-342) Single-sided Printable PermaSleeve Markers

Order Reference	Markers Per Box	Range of Wire Dia.		Approx. Wire Gauge**	Marker Width (mm)	Marker Height (mm)	Vertical Repeat (mm) C	Recommended Ribbon Series
		Min. mm	Max. mm		A	B		
38.10 mm Marker Width								
PS-094-150-WT	2 500	0.58 – 2.03		28-18	38.10	4.60	12.70	R-4300
PS-094-150-WT-S	500	0.58 – 2.03		28-18	38.10	4.60	12.70	R-4300
PS-125-150-WT	2 500	1.17 – 2.79		22-16	38.10	6.00	12.70	R-4300
PS-125-150-WT-S	500	1.17 – 2.79		22-16	38.10	6.00	12.70	R-4300
PS-187-150-WT	2 500	1.57 – 3.81		18-12	38.10	8.50	15.88	R-4300
PS-187-150-WT-S	500	1.57 – 3.81		18-12	38.10	8.50	15.88	R-4300
PS-250-150-WT	2 500	2.39 – 5.46		16-10	38.10	11.15	19.05	R-4300
PS-250-150-WT-S	500	2.39 – 5.46		16-10	38.10	11.15	19.05	R-4300
PS-375-150-WT	1 000	3.18 – 8.13		12-6	38.10	16.40	25.40	R-4300
PS-375-150-WT-S	250	3.18 – 8.13		12-6	38.10	16.40	25.40	R-4300
PS-500-150-WT	500	4.75 – 11.43		8-1	38.10	21.60	31.75	R-4300
PS-500-150-WT-S	250	4.75 – 11.43		8-1	38.10	21.60	31.75	R-4300
50.80 mm Marker Width								
PS-094-2-WT	2 500	0.58 – 2.03		28-18	50.80	4.60	12.70	R-4300
PS-094-2-WT-S	500	0.58 – 2.03		28-18	50.80	4.60	12.70	R-4300
PS-125-2-WT	2 500	1.17 – 2.79		22-16	50.80	6.00	12.70	R-4300
PS-125-2-WT-S	500	1.17 – 2.79		22-16	50.80	6.00	12.70	R-4300
PS-187-2-WT	2 500	1.57 – 3.81		18-12	50.80	8.50	15.88	R-4300
PS-187-2-WT-S	500	1.57 – 3.81		18-12	50.80	8.50	15.88	R-4300
PS-250-2-WT	2 500	2.39 – 5.46		16-10	50.80	11.15	19.05	R-4300
PS-250-2-WT-S	500	2.39 – 5.46		16-10	50.80	11.15	19.05	R-4300
PS-375-2-WT	1 000	3.18 – 8.13		12-6	50.80	16.40	25.40	R-4300
PS-375-2-WT-S	250	3.18 – 8.13		12-6	50.80	16.40	25.40	R-4300
PS-500-2-WT	500	4.75 – 11.43		8-1	50.80	21.60	31.75	R-4300
PS-500-2-WT-S	250	4.75 – 11.43		8-1	50.80	21.60	31.75	R-4300