





Valve Connectors

Field attachable connectors - Form C - Industrial



Technical drawing	2poles + P.E.	3poles + P.E.	2poles + P.E., UL approval
			

Product description	DIN valve connectors	DIN valve connectors	DIN valve connectors
Connector type	DIN valve connectors	DIN valve connectors	DIN valve connectors
Conforms to	Industrial	Industrial	Industrial
Construction type	C	C	C

Description	Square micro connector P2 series complete with gasket and fixing screw. Connector without electronic.	Square micro connector P2 series complete with gasket and fixing screw. Connector without electronic.	Square micro connector P2 series, UL approval, complete with gasket and fixing screw. Connector without electronic.
Contacts spacing	9.4mm	9.4mm	9.4mm
Number of contacts	2poles + P.E.	3poles + P.E.	2poles + P.E.
Earth positioning	H.6 (turnable)	H.6 (turnable)	H.6 (turnable)
Housing colour	Black	Black	Black
Housing height	26mm	26mm	26mm
Cable gland	PG7	PG7	PG7
Gasket type	Profiled NBR gasket	Profiled NBR gasket	Profiled NBR gasket

Technical data	Screw contacts	Screw contacts	Screw contacts
Type of termination	Screw contacts	Screw contacts	Screw contacts
Contact screw torque	0.25 N*m	0.25 N*m	0.25 N*m
Rated voltage	250V AC/ 300VDC	250V AC/ 300VDC	250V AC/ 300VDC
Circuit type	-	-	-
Led colour	-	-	-
Suitable cable	ø cable 4-6mm	ø cable 4-6mm	ø cable 4-6mm
Central fixing screw	M3 L=28mm	M3 L=28mm	M3 L=28mm
Central fixing screw material	Iron+Zinc plated	Iron+Zinc plated	Iron+Zinc plated
Central screw torque	0.5 N*m	0.5 N*m	0.5 N*m

Packaging	100pcs / box	100pcs / box	100pcs / box
Qty/Box	100pcs / box	100pcs / box	100pcs / box

Other accessories options	See accessories section		
See accessories section	See accessories section		