


Highly Flexible Plastic Protection Conduit; Liquid Tight; Plastic Coated Spring Steel Wire



Properties

IP 54 to EN/IEC 60529

Self-locking conduit assembly

Inner socket protects cables from damage

One-piece

Good resistance to chemicals

Flame-retardant

Designed according to EN 60204 for plant and mechanical engineering

Thread reference: M (metric) to EN60423, P (PG) to DIN 40430

Conforms to RoHS guideline

Temperature range

-10 °C to 110 °C

Delivery variants

Grey (standard)

Special colours: Full coloured

Design material

Body plastic (pp); rotary plating (pp) connecting thread with hexagonal spanner surface

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Conduit Connector With Integrated Inner Socket; Rotary Connecting Thread

Nominal Length	Gewinde metrisch M EN 60423	Gewinde PG DIN 40431	Thread Length E	Total Length L	Wrench Size across Flats	O.D. D	I.D. d	Weight	PU Pcs
10	M 12 x 1,5	-	7,5	41,0	17	18,7	5,5	0,5	10
10	M 12 x 1,5	-	7,5	41,0	17	18,7	5,5	0,5	50
14	M16 x 1,5	-	8,5	44,0	20	22,0	8,8	0,7	10
14	M16 x 1,5	-	8,5	44,0	20	22,0	8,8	0,7	50
17	M20 x 1,5	-	9,0	47,5	24	26,4	11,1	0,9	10
17	M20 x 1,5	-	9,0	47,5	24	26,4	11,1	0,9	50
21	M25 x 1,5	-	10,0	52,0	30	32,8	14,8	1,5	10
21	M25 x 1,5	-	10,0	52,0	30	32,8	14,8	1,5	50
27	M32 x 1,5	-	11,0	55,0	36	39,3	19,4	2,1	10
27	M32 x 1,5	-	11,0	55,0	36	39,3	19,4	2,1	25
36	M40 x 1,5	-	12,0	57,8	46	50,2	27,9	3,4	2
36	M40 x 1,5	-	12,0	57,8	46	50,2	27,9	3,4	25
45	M50 x 1,5	-	13,0	61,0	55	60,0	35,6	4,9	2
45	M50 x 1,5	-	13,0	61,0	55	60,0	35,6	4,9	25
56	M63 x 1,5	-	13,5	63,0	65	71,0	45,9	7,0	2
56	M63 x 1,5	-	13,5	63,0	65	71,0	45,9	7,0	10
10	-	PG 7	7,5	41,0	17	18,7	5,5	0,5	10
10	-	PG 7	7,5	41,0	17	18,7	5,5	0,5	50
14	-	PG 9	8,5	44,0	20	22,0	8,8	0,7	10
14	-	PG 9	8,5	44,0	20	22,0	8,8	0,7	50
17	-	PG 11	9,0	47,5	24	26,4	11,1	0,9	10
17	-	PG 11	9,0	47,5	24	26,4	11,1	0,9	50
19	-	PG 13,5	9,5	49,5	27	29,7	13,0	1,2	10
19	-	PG 13,5	9,5	49,5	27	29,7	13,0	1,2	50
21	-	PG 16	10,0	52,0	30	32,8	14,8	1,5	10
21	-	PG 16	10,0	52,0	30	32,8	14,8	1,5	50
27	-	PG 21	11,0	55,0	36	39,3	19,4	2,1	10
27	-	PG 21	11,0	55,0	36	39,3	19,4	2,1	25
36	-	PG 29	12,0	57,8	46	50,2	27,9	3,4	2
36	-	PG 29	12,0	57,8	46	50,2	27,9	3,4	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com



Plastic Conduit Connector With Integrated Inner Socket; Rotary Connecting Thread

Nominal Length	Gewinde metrisch M EN 60423	Gewinde PG DIN 40431	Thread Length E	Total Length L	Wrench Size across Flats	O.D. D	I.D. d	Weight	PU Pcs
45	-	PG 36	13,0	61,0	55	60,0	35,6	4,9	2
45	-	PG 36	13,0	61,0	55	60,0	35,6	4,9	25
52	-	PG 42	13,0	62,3	62	67,5	41,9	6,1	2
52	-	PG 42	13,0	62,3	62	67,5	41,9	6,1	10
56	-	PG 48	13,5	63,0	65	71,0	45,9	7,0	2
56	-	PG 48	13,5	63,0	65	71,0	45,9	7,0	10

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com