


Abrasion-proof, oil resistant and polyurethane coated metal protection conduit; extremely robust and liquid tight: double folded metal profile



Properties

IP 68 to EN/IEC 60529

Good screening factor (EMC)

Highly flexible

Highly abrasion resistant

Increased resistance to tear, pressure and impact

Microbe and hydrolysis resistant

Good resistance to oil, gasoline and chemicals

Very good low temperature flexibility

Temperature range

-40 °C to 90 °C

Short time to 125 °C

Delivery variants

Further diameters and lengths available on request

Special colours: Full coloured

Customer-specific branding

Design material

Profiled metal strip, galvanised steel; twice rolled profile; wall; special premium ether-polyurethane (Pre-PUR)

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Abrasion-proof, oil resistant and polyurethane coated metal protection conduit; extremely robus and liquid tight: double folded metal profile

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Weight kg/m	PU
10	7	10	44	0,13	10
10	7	10	44	0,13	50
14	10	14	48	0,16	10
14	10	14	48	0,16	50
17	13	17	65	0,28	10
17	13	17	65	0,28	50
19	15	19	70	0,32	10
19	15	19	70	0,32	50
21	17	21	77	0,35	10
21	17	21	77	0,35	50
27	22	27	101	0,45	10
27	22	27	101	0,45	50
36	30	36	146	0,85	10
36	30	36	146	0,85	25
45	38	45	188	1,10	10
45	38	45	188	1,10	25
52	46	52	225	1,30	10
52	46	52	225	1,30	25
56	50	56	240	1,40	10
56	50	56	240	1,40	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

