EASY TO USE DURABLE LIGHTWEIGHT

- Sealed up to IP68
- Over 5,000 mating cycles
- Resistant to large temperature variations
- Clear coding for easy operation

Ideally suited for:

- Medical applications
- Industrial & instrumentation
- Food and pharmaceutical processing







2 TO 27 CONTACTS

BODY STYLES

405

(2 to 27 contacts)



4032

(2 to 19 contacts)



PLUGS

CABLE MOUNTED		
BODY STYLES	S	SI
Locking system	Push-pull	Push-pull
Sealing	IP50 / IP67	IP50 / IP67
Design	Standard	Standard
Integral shielding	Yes	No

RECEPTACLES

PANEL FRONT **MOUNTED**



BODY STYLES	DBP	
Sealing	IP50	
Design	Standard	

PLUGS

CABLE MOUNTED



BODY STYLES	SI
Locking system	Push-pull
Sealing	IP50 / IP68
Design	Standard
Integral shielding	No

RECEPTACLES

PANEL FRONT MOUNTED





BODY STYLES	DBP	DBPO	
Sealing	IP50	IP68	
Design	Standard	Standard	

PERFORMANCE & RELIABILITY



- Sterilizable* by Autoclave, Cidex, EtO, gamma radiation, Steris® or Sterrad®
- Integrated into FDA-approved medical devices
- Lightweight and easy to handle
- EMI/RFI shielding for reliable data transmission



