

RECEPTACLES 6.3 (.250) SERIES, STRAIGHT TYPE, STANDARD SELF-LOCKING, CONNECTOR DISCONNECTION

Receptacles 6.3 (.250) series, straight type, standard self-locking, connector disconnection

Terminal version	**On reel**
Terminal type	**Receptacles**
Mating tab width	**6.3**
Crimping press	**On request**







Partnumber	Wire size	AWG	Tab thickn.	Material	Mat. thickn.	Parts x reel	Ø Insul.	Approvals
32472230	1 to 2.5	18-14	0.8	Bronze	0.4	7000	3 to 4.3	UL
32472424	2.5 to 5	14-10	0.8	Steel Ni	0.4	6000	3.6 to 5	UL
32472024	0.5 to 1	20-18	0.8	Steel Ni	0.4	8000	1.8 to 2.5	UL
32472030	0.5 to 1	20-18	0.8	Bronze	0.4	8000	1.8 to 2.5	UL
32472202	1 to 2.5	18-14	0.8	Brass Sn	0.4	7000	3 to 4.3	UL
32472000	0.5 to 1	20-18	0.8	Brass	0.4	8000	1.8 to 2.5	UL
32472232	1 to 2.5	18-14	0.8	Bronze Sn	0.4	7000	3 to 4.3	UL
32472402	2.5 to 5	14-10	0.8	Brass Sn	0.4	6000	3.6 to 5	UL
32472432	2.5 to 5	14-10	0.8	Bronze Sn	0.4	6000	3.6 to 5	UL

Partnumber	Wire size	AWG	Tab thickn.	Material	Mat. thickn.	Parts x reel	Ø Insul.	Approvals
32472430	2.5 to 5	14-10	0.8	Bronze	0.4	6000	3.6 to 5	UL
32472224	1 to 2.5	18-14	0.8	Steel Ni	0.4	7000	3 to 4.3	UL
32472200	1 to 2.5	18-14	0.8	Brass	0.4	7000	3 to 4.3	UL
32472002	0.5 to 1	20-18	0.8	Brass Sn	0.4	8000	1.8 to 2.5	UL
32472032	0.5 to 1	20-18	0.8	Bronze Sn	0.4	8000	1.8 to 2.5	UL
32472400	2.5 to 5	14-10	0.8	Brass	0.4	6000	3.6 to 5	UL