


Abrasion-proof, oil resistant and polyurethane coated metal protection conduit; very robust and liquid tight: hooked metal profile



Properties

IP 68 to EN/IEC 60529

Good resistance to oil, gasoline and chemicals

Good resistance to alkalis and acids

Increased resistance to tear, pressure and impact

Flame-retardant

Conforms to RoHS guideline

Microbe and hydrolysis resistant

Highly flexible & Highly abrasion resistant

Temperature range

-40 °C to 90 °C

Short time to 125 °C

Delivery variants

Further diameters and lengths available on request

Special colours: full coloured

Customer-specific branding

Design material

Profiled metal strip, galvanised steel; hooked profile; wall; wall: Special premium ether-polyurethane (Pre-PUR)

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Abrasion-proof, oil resistant and polyurethane coated metal protection conduit; very robust and liquid tight: hooked metal profile

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Dyn. Bending Radius	Weight kg/m	PU
10	7	10	40	40	0,08	10
10	7	10	40	40	0,08	50
14	10	14	46	48	0,14	10
14	10	14	46	48	0,14	50
17	13	17	55	55	0,17	10
17	13	17	55	55	0,17	50
19	15	19	60	60	0,19	10
19	15	19	60	60	0,19	50
21	17	21	75	75	0,23	10
21	17	21	75	75	0,23	50
27	22	27	90	90	0,38	10
27	22	27	90	90	0,38	50
36	29	36	110	110	0,60	10
36	29	36	110	110	0,60	25
45	38	45	140	140	0,80	10
45	38	45	140	140	0,80	25
52	45	52	165	165	1,00	10
52	45	52	165	165	1,00	25
56	49	56	175	175	1,08	10
56	49	56	175	175	1,08	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com