
Highly Flexible Plastic Protection Conduit; Liquid Tight; Plastic Coated Spring Steel Wire





Properties

IP68 to EN/IEC 60529
Highly flexible + compressible
Good resistance to alkalis and acids
Good resistance to chemicals
Flame-retardant according to: UL94 HB
Approved to DIN EN 50369
Conforms to RoHs guideline

Temperature range

-20 °C to 70 °C

Short time to 80 °C

Delivery variants

Futher diameters and lenghts available on request

Grey (standard)

Special colours: Full coloured

Custom-specific branding

Design material

Plastic coating spring steel wire; wall: high grade soft PVC; wall thickness 0.4 - 0.9 mm approx. depending on diameter

Get in contact with our team in The Netherlands or Belgium

The Netherlands Freddy van Riemsdijkweg 7 5657 EE Eindhoven **Belgium** Grauwmeer 1/45 Bus 43 B-3001 Heverlee

+31 (0)40 20 88 088 sales@avt-connecting.com www.avt-connecting.com +32 (0)16 400 500 sales@avt-connecting.be www.avt-connecting.com



Highly Flexible Plastic Protection Conduit; Liquid Tight; Plastic Coated Spring Steel Wire

Nominal width connecting part mm	I.D. mm	O.D. mm	Bending Ra- dius (middle of hose) mm	Dyn. Bending Radius acc. to Norm	Weight kg/m	PU m
10	7	10	10	28	0,05	10
10	7	10	10	28	0,05	50
14	10	14	14	40	0,08	10
14	10	14	14	40	0,08	50
17	13	17	17	48	0,12	10
17	13	17	17	48	0,12	50
19	15	19	19	55	0,13	10
19	15	19	19	55	0,13	50
21	16	21	21	60	0,14	10
21	16	21	21	60	0,14	50
27	21	27	27	75	0,26	10
27	21	27	27	75	0,26	50
36	30	36	36	100	0,35	10
36	30	36	36	100	0,35	25
45	38	45	45	124	0,54	10
45	38	45	45	124	0,54	25
52	44	52	52	143	0,67	10
52	44	52	52	143	0,67	25
56	48	56	56	154	0,70	10
56	48	56	56	154	0,70	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands Freddy van Riemsdijkweg 7 5657 EE Eindhoven

+31 (0)40 20 88 088 sales@avt-connecting.com www.avt-connecting.com **Belgium** Grauwmeer 1/45 Bus 43 B-3001 Heverlee

+32 (0)16 400 500 sales@avt-connecting.be www.avt-connecting.com

