

RUTASEAL PG Grommets, EPDM



Material

EPDM

Resistant to chemicals and weatherproof.
Suitable for holes in materials of 0,5 - 4 mm thickness.
Quick and simple assembly without the use of tools.

Mode of protection

IP67 acc. to EN 60529

Temperature range

-40°C....+110°C

Test standard

EMKO TUI (03-SEC) FI 001/84

Semko report

410375

Halogen-Free

Purchase number	Size	For cable / pipe Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Pcs pack
Grey RAL 7001								
14438220	PG7/12,5	3 - 5	13	0,5 - 2	20	12,6	5,4	50
14438221	PG9/15,2	5 - 7	16	1 - 4	21	17,8	10,3	50
14438222	PG11/18,6	7 - 10	19	1 - 4	24	19,8	12,7	50
14438223	PG16/22,5	10 - 14	23	1 - 4	28	21,6	14,7	50
14438224	PG21/28,3	14 - 20	29	1 - 4	35	24,6	17,6	25
14438225	PG29/37,0	20 - 26	38	1 - 4	46	28,5	20	25
14438226	PG36/47,0	26 - 35	48	1 - 4	58	34,9	23,9	10
Black RAL 9005								
14438228	PG7/12,5	3 - 5	13	0,5 - 2	20	12,6	5,4	50
14438229	PG9/15,2	5 - 7	16	1 - 4	21	17,8	10,3	50
14438230	PG11/18,6	7 - 10	19	1 - 4	24	19,8	12,7	50
14438231	PG16/22,5	10 - 14	23	1 - 4	28	21,6	14,7	50
14438232	PG21/28,3	14 - 20	29	1 - 4	35	24,6	17,6	25
14438233	PG29/37,0	20 - 26	38	1 - 4	46	28,5	20	25
14438234	PG36/47,0	26 - 35	48	1 - 4	58	34,9	23,9	10
Light grey RAL 7035								
14438212	PG7/12,5	3 - 5	13	0,5 - 2	20	12,6	5,4	50
14438213	PG9/15,2	5 - 7	16	1 - 4	21	17,8	10,3	50
14438214	PG11/18,6	7 - 10	19	1 - 4	24	19,8	12,7	50
14438215	PG16/22,5	10 - 14	23	1 - 4	28	21,6	14,7	50
14438216	PG21/28,3	14 - 20	29	1 - 4	35	24,6	17,6	25
14438217	PG29/37,0	20 - 26	38	1 - 4	46	28,5	20	25
14438218	PG36/47,0	26 - 35	48	1 - 4	58	34,9	23,9	10

