

RUTASEAL Light Metric Grommets, EPDM



Material EPDM
Resistant to chemicals and weatherproof.
Suitable for holes in materials of 1 - 4 mm thickness.
Quick and simple assembly without the use of tools.

Mode of protection IP67 acc. to EN 60529
Temperature range -40°C...+110°C
Test standard SEMKO 44:1984
Semko report 300965
Halogen-Free



RUTASEAL LIGHT is designed for strip lighting manufacturers and similar applications. Less material makes it lighter and easier to install, while providing IP67 protection.

| Purchase number | Size | For cable / pipe Ø mm | A mm | B mm | Da mm | H mm | H1 mm | Pcs pack |
|----------------------------|------|-----------------------|------|-------|-------|------|-------|----------|
| Grey RAL 7001 | | | | | | | | |
| 14438326 | M16 | 5 - 9 | 16,5 | 1 - 4 | 21 | 17,5 | 11 | 50 |
| 14438327 | M20 | 8 - 13 | 20,5 | 1 - 4 | 25,5 | 19,6 | 13,4 | 50 |
| 14438328 | M25 | 11 - 17 | 25,5 | 1 - 4 | 30,5 | 20,9 | 15,3 | 50 |
| Black RAL 9005 | | | | | | | | |
| 14438330 | M16 | 5 - 9 | 16,5 | 1 - 4 | 21 | 17,5 | 11 | 50 |
| 14438331 | M20 | 8 - 13 | 20,5 | 1 - 4 | 25,5 | 19,6 | 13,4 | 50 |
| 14438332 | M25 | 11 - 17 | 25,5 | 1 - 4 | 30,5 | 20,9 | 15,3 | 50 |
| Light grey RAL 7035 | | | | | | | | |
| 14438334 | M16 | 5 - 9 | 16,5 | 1 - 4 | 21 | 17,5 | 11 | 50 |
| 14438335 | M20 | 8 - 13 | 20,5 | 1 - 4 | 25,5 | 19,6 | 13,4 | 50 |
| 14438336 | M25 | 11 - 17 | 25,5 | 1 - 4 | 30,5 | 20,9 | 15,3 | 50 |

