

RUTASEAL Metric Grommets, EPDM



Material

EPDM
Resistant to chemicals and weatherproof.
Suitable for holes in materials of 0,5 - 4 mm thickness.
Quick and simple assembly without the use of tools.

Mode of protection

IP67 acc. to EN 60529

Temperature range

-40°C....+110°C

Test standard



SEMKO 44:1984

Semko report

0211038/01-07

Halogen-Free

Purchase number	Size	For cable / pipe Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Pcs pack
Grey RAL 7001								
14438233	M12	4 - 7	12,5	0,5 - 2	20	12,8	5,6	50
14438234	M16	5 - 9	16,5	1 - 4	21	17,7	11	50
14438235	M20	8 - 13	20,5	1 - 4	25,5	20	13,4	50
14438236	M25	11 - 17	25,5	1 - 4	30,5	21,3	15,3	50
14438237	M32	15 - 20	32,5	1 - 4	38,5	24,6	18,6	25
14438238	M40	19 - 28	40,5	1 - 4	48,5	29,5	21,7	25
14438239	M50	27 - 35	50,5	1 - 4	60,5	34,8	25	10
Black RAL 9005								
14438293	M12	4 - 7	12,5	0,5 - 2	20	12,8	5,6	50
14438294	M16	5 - 9	16,5	1 - 4	21	17,7	11	50
14438295	M20	8 - 13	20,5	1 - 4	25,5	20	13,4	50
14438296	M25	11 - 17	25,5	1 - 4	30,5	21,3	15,3	50
14438297	M32	15 - 20	32,5	1 - 4	38,5	24,6	18,6	25
14438298	M40	19 - 28	40,5	1 - 4	48,5	29,5	21,7	25
14438299	M50	27 - 35	50,5	1 - 4	60,5	34,8	25	10
Light grey RAL 7035								
14438303	M12	4 - 7	12,5	0,5 - 2	20	12,8	5,6	50
14438304	M16	5 - 9	16,5	1 - 4	21	17,7	11	50
14438305	M20	8 - 13	20,5	1 - 4	25,5	20	13,4	50
14438306	M25	11 - 17	25,5	1 - 4	30,5	21,3	15,3	50
14438307	M32	15 - 20	32,5	1 - 4	38,5	24,6	18,6	25
14438308	M40	19 - 28	40,5	1 - 4	48,5	29,5	21,7	25
14438309	M50	27 - 35	50,5	1 - 4	60,5	34,8	25	10



Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com





RUTASEAL Metric Grommets, Chloroprene



Material Chloroprene
 Resistant to chemicals, ageing and weatherproof.
 Suitable for holes in materials of 0,5 - 4 mm thickness.
 Quick and simple assembly without the use of tools.

Mode of protection IP67 acc. to EN 60529
Temperature range -30°C...+100°C
Test standard EMKO TUI (03-SEC) FI 001/84
Semko report 410375
DNV report E-8009

Purchase number	Size	For cable / pipe Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Pcs pack
Black RAL 9005								
14438253	M12	4 - 7	12,5	0,5 - 2	20	12,8	5,6	50
14438254	M16	5 - 9	16,5	1 - 4	21	17,7	11	50
14438255	M20	8 - 13	20,5	1 - 4	25,5	20	13,4	50
14438256	M25	11 - 17	25,5	1 - 4	30,5	21,3	15,3	50
14438257	M32	15 - 20	32,5	1 - 4	38,5	24,6	18,6	25
14438258	M40	19 - 28	40,5	1 - 4	48,5	29,5	21,7	25
14438259	M50	27 - 35	50,5	1 - 4	60,5	34,8	25	10



Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
 5657 EE Eindhoven

+31 (0)40 20 88 088
 sales@avt-connecting.com
 www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
 B-3001 Heverlee

+32 (0)16 400 500
 sales@avt-connecting.be
 www.avt-connecting.com

