

RUTASEAL PG Grommets, Chloroprene



Material

Chloroprene

Resistant to chemicals, ageing and weatherproof.

Suitable for holes in materials of 0,5 - 4 mm thickness.

Quick and simple assembly without the use of tools.

Mode of protection

IP67 acc. to EN 60529

Temperature range

-30°C....+100°C

Test standard

EMKO TUI (03-SEC) FI 001/84

Semko report

410375

DNV report

E-8009

Purchase number	Size	For cable / pipe Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Pcs pack
Black RAL 9005								
14438242	PG7/12,5	3 - 5	13	0,5 - 2	20	12,6	5,4	50
14438243	PG9/15,2	5 - 7	16	1 - 4	21	17,8	10,3	50
14438244	PG11/18,6	7 - 10	19	1 - 4	24	19,8	12,7	50
14438245	PG16/22,5	10 - 14	23	1 - 4	28	21,6	14,7	50
14438246	PG21/28,3	14 - 20	29	1 - 4	35	24,6	17,6	25
14438247	PG29/37,0	20 - 26	38	1 - 4	46	28,5	20	25
14438248	PG36/47,0	26 - 35	48	1 - 4	58	34,9	23,9	10

