


Plastic Conduit Connector With Integrated Inner Socket; Rotary Mounting Flange



Properties

IP 54 to EN/IEC 60529

Self-locking conduit assembly

Inner socket protects cables from damage

Easily and quickly fitted

One-piece

Good resistance to chemicals

Flame-retardant

Designed according to EN 60204 for plant and mechanical engineering

Thread reference: M (metric) to EN60423, P (PG) to DIN 40430

Temperature range

-10 °C to 110 °C

Delivery variants

Grey (standard)

Special colours: Full coloured

Design material

Rotary plastic (pp) mounting flange with fastening holes

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Conduit Connector With Integrated Inner Socket; Rotary Mounting Flange

Nominal Length tube mm	Total Length L mm	Ø-M mm	Length L2 mm	O.D. D mm	I.D. d mm	X mm	Weight kg/100pcs.	PU Pcs
10	41,0	5,7	10,5	36,0	5,5	25	0,5	10
10	41,0	5,7	10,5	36,0	5,5	25	0,5	50
14	44,0	5,7	12,5	40,0	8,8	29	0,8	10
14	44,0	5,7	12,5	40,0	8,8	29	0,8	50
17	47,5	5,7	13,0	50,0	11,1	37	1,0	10
17	47,5	5,7	13,0	50,0	11,1	37	1,0	50
19	49,5	5,7	14,0	50,0	13,0	37	1,3	10
19	49,5	5,7	14,0	50,0	13,0	37	1,3	50
21	52,0	5,7	15,5	50,0	14,8	37	1,6	10
21	52,0	5,7	15,5	50,0	14,8	37	1,6	50
27	55,0	5,7	16,5	57,0	19,4	43	2,1	10
27	55,0	5,7	16,5	57,0	19,4	43	2,1	25
36	57,8	6,7	17,0	67,0	27,9	53	3,3	2
36	57,8	6,7	17,0	67,0	27,9	53	3,3	25
45	61,0	6,7	18,5	80,0	35,6	65	4,6	2
45	61,0	6,7	18,5	80,0	35,6	65	4,6	25
52	62,3	6,7	19,0	88,0	41,9	72	5,8	2
52	62,3	6,7	19,0	88,0	41,9	72	5,8	10
56	63,0	6,7	19,0	93,0	45,9	76	6,9	2
56	63,0	6,7	19,0	93,0	45,9	76	6,9	10

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Conduit Connector With Integrated Inner Socket; Rotary Connecting Thread

Nominal Length	Gewinde metrisch M EN 60423	Gewinde PG DIN 40431	Thread Length E	Total Length L	Wrench Size across Flats	O.D. D	I.D. d	Weight	PU Pcs
45	-	PG 36	13,0	61,0	55	60,0	35,6	4,9	2
45	-	PG 36	13,0	61,0	55	60,0	35,6	4,9	25
52	-	PG 42	13,0	62,3	62	67,5	41,9	6,1	2
52	-	PG 42	13,0	62,3	62	67,5	41,9	6,1	10
56	-	PG 48	13,5	63,0	65	71,0	45,9	7,0	2
56	-	PG 48	13,5	63,0	65	71,0	45,9	7,0	10

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com