


Plastic Tube Connector, Rigid Connecting Thread



Properties

IP 65 to EN/IEC 60529

IP 65 to EN/IEC 60529 assembled with o-ring sealing in first groove of the conduit (size 50mm in the first and second groove)

Easily and quickly fitted

Re-usable

One piece

Vibration resistant

Good resistance to oil, gasoline and chemicals

Good resistance to alkalis and acids

Good resistance to chemicals

Designed according to EN 60204 for plant and mechanical engineering

Conforms to RoHS guideline

Temperature range

-40 °C to +120 °C

Short time to 130 °C

Delivery variants

Further diameters and lengths available on request

Grey (standard), Black (standard)

Design material

Body; plastic (PA6), rigid connecting thread with hexagonal spanner surface

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Tube Connector, Rigid Connecting Thread

Nominal Length tube mm	Outer thread metric M EN 60423	thread PG DIN 40430	Total Length L mm	Wrench Size across Flats mm	O.D. D mm	I.D. d mm	Weight kg/100pcs.	PU Pcs
8,5	M 12 x 1,5	-	35	16	23	7,5	0,41	50
10	M 16 x 1,5	-	36	17	24,5	11	0,469	50
13	M 20 x 1,5	-	38	20	29	15,2	0,636	50
17	M 25 x 1,5	-	43	27	38,5	19,1	1,287	50
29	M 32 x 1,5	-	52	41	55,5	25,5	2,852	20
37	M 40 x 1,5	-	62	50	66,5	34	4,581	10
50	M 50 x 1,5	-	68	64	80	43,5	7,697	5
50	M 63 x 1,5	-	68	64	80	53,2	7,79	5
10	M 12 x 1,5	-	36	17	24,5	7,5	0,439	50
13	M 16 x 1,5	-	38	20	29	11	0,628	50
17	M 20 x 1,5	-	43	27	38,5	15,4	1,205	50
23	M 25 x 1,5	-	48	34	48,5	19,1	1,969	25
8,5	-	PG 7	35	16	23	7,5	0,433	50
10	-	PG 7	36	17	24,5	9	0,431	50
10	-	PG 9	36	17	24,5	11	0,455	50
10	-	PG 11	36	17	24,5	12,5	0,466	50
13	-	PG 9	38	20	29	11	0,6	50
13	-	PG 11	38	20	29	14,5	0,62	50
13	-	PG 13,5	38	20	29	15,2	0,665	50
17	-	PG 13,5	43	27	38,5	15,4	1,237	50
17	-	PG 16	43	27	38,5	18,1	1,219	50
23	-	PG 21	48	34	48,5	23	1,955	25
29	-	PG 29	52	41	55,5	31	2,839	20
37	-	PG 36	62	50	66,5	39	4,798	10
50	-	PG 48	68	64	80	43,5	7,617	5
8,5	M 12 x 1,5	-	35	16	23	7,5	0,41	50
10	M 16 x 1,5	-	36	17	24,5	11	0,469	50
13	M 20 x 1,5	-	38	20	29	15,2	0,636	50

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Plastic Tube Connector, Rigid Connecting Thread

Nominal Length tube mm	Outer thread metric M EN 60423	thread PG DIN 40430	Total Length L mm	Wrench Size across Flats mm	O.D. D mm	I.D. d mm	Weight kg/100pcs.	PU Pcs
17	M 25 x 1,5	-	43	27	38,5	19,1	1,287	50
29	M 32 x 1,5	-	52	41	55,5	25,5	2,852	20
37	M 40 x 1,5	-	62	50	66,5	34	4,581	10
50	M 50 x 1,5	-	68	64	80	43,5	7,697	5
50	M 63 x 1,5	-	68	64	80	53,2	7,79	5
10	M 12 x 1,5	-	36	17	24,5	7,5	0,439	50
13	M 16 x 1,5	-	38	20	29	11	0,628	50
17	M 20 x 1,5	-	43	27	38,5	15,4	1,205	50
23	M 25 x 1,5	-	48	34	48,5	19,1	1,969	25
8,5	-	PG 7	35	16	23	7,5	0,433	50
10	-	PG 7	36	17	24,5	9	0,431	50
10	-	PG 9	36	17	24,5	11	0,455	50
10	-	PG 11	36	17	24,5	12,5	0,466	50
13	-	PG 9	38	20	29	11	0,6	50
13	-	PG 11	38	20	29	14,5	0,62	50
13	-	PG 13,5	38	20	29	15,2	0,665	50
17	-	PG 13,5	43	27	38,5	15,4	1,237	50
17	-	PG 16	43	27	38,5	18,1	1,219	50
23	-	PG 21	48	34	48,5	23	1,955	25
29	-	PG 29	52	41	55,5	31	2,839	20
37	-	PG 36	62	50	66,5	39	4,798	10
50	-	PG 48	68	64	80	43,5	7,617	5

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com